



# BEAM CLAMP ROLLERS

Mathey Dearman's Beam Clamp Rollers are used for a variety of industries and applications, typically for installation of pipes into racks at Refineries, Power Stations and other Industrial Plants.

All the Mathey Dearman Beam Clamp Rollers are designed to be light weight, with I-beam clamps for quick installation and various roller head options so that all sizes and weights of pipe can be easily, safely and efficiently installed.

## Features and advantages

- Six configurations from 1 - 10 tons capacity
- Three sizes for 2" - 60" pipe diameters
- Urethane wheels with sealed bearings
- Easy to replace wheels, bolt off and on in seconds
- Comes ready to use on Stainless Steel
- Convenient and safe carry handles on all models
- Safety leash included with all models



| PART NO.                | 2110                                      | 2110HD                                    | 2125                                       | 2125HD                                     | 2135                                       | 2135HD                                     |
|-------------------------|---|---|--|--|--|--|
| Load Capacity           | 1 Ton<br>1,016 kg<br>2,240 lbs.           | 3 Tons<br>3,048 kg<br>6,720 lbs.          | 5 Tons<br>5,080 kg<br>11,200 lbs.          | 10 Tons<br>10,160 kg<br>22,400 lbs.        | 5 Tons<br>5,080 kg<br>11,200 lbs.          | 10 Tons<br>10,160 kg<br>22,400 lbs.        |
| Pipe Diameter Range     | 2" - 24"<br>50 - 610 mm                   | 2" - 24"<br>50 - 610 mm                   | 4" - 48"<br>100 - 1,220 mm                 | 4" - 48"<br>100 - 1,220 mm                 | 16" - 60"<br>400 - 1,530 mm                | 16" - 60"<br>400 - 1,530 mm                |
| Complete Unit Weight    | 27 kg<br>59 lbs.                          | 43 kg<br>95 lbs.                          | 59 kg<br>130 lbs.                          | 82 kg<br>180 lbs.                          | 66 kg<br>145 lbs.                          | 91 kg<br>200 lbs.                          |
| Footprint L x W x H     | 16.5" x 20.5" x 8"<br>41.9 x 52 x 20.3 cm | 16.5" x 20.5" x 8"<br>41.9 x 52 x 20.3 cm | 19" x 30" x 8.75"<br>48.3 x 76.2 x 22.2 cm | 19" x 30" x 8.75"<br>48.3 x 76.2 x 22.2 cm | 21" x 34" x 8.75"<br>53.3 x 86.4 x 22.2 cm | 21" x 34" x 8.75"<br>53.3 x 86.4 x 22.2 cm |
| Beam Flange Width Range | 6" - 12"<br>150 x 300 mm                  | 6" - 12"<br>150 x 300 mm                  | 6" - 12"<br>150 x 300 mm                   | 6" - 12"<br>150 x 300 mm                   | 6" - 12"<br>150 x 300 mm                   | 6" - 12"<br>150 x 300 mm                   |

Roller Maintains at Center of I Beam

